



Ash Transparent Baltic

Product details / Technical properties

Article number	10135087 (AS2L85TY)	Bevel	without bevel	Moisture content	5-9%
Wood	Ash	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Baltic	Surface structure	sanded	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	1,89	PCP content	NPD
Format	23mm Longstrip 3-Strip	Boards per carton	4	Brinell Value (N/mm²)	36
Dimensions	23 x 215 x 2200 mm	Weight per carton (kg)	23	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	85,05	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	45	Thermal conductivity (W/(m*K))	
Connection	T/G	Weight per pallet (kg)	1035	Thermal resistance (m²*K)/W	
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	FSC™ Mix 70%	Antislip performance (DIN)	R9
Appearance	Light floors	Biological durability	Class 1	Nobb.number	
Colour	Transparent	Density	>= 500kg/m³	EAN Code	7035580211105



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.