




Oak Country

Product details / Technical properties

Article number	10135527 (EI2745PY)	Bevel	square edged	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	E 1
Grading	Country	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	1,83	PCP content	NPD
Format	Plank 23mm Plank 139	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions	23 x 139 x 2200 mm	Weight per carton (kg)	22,5	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	89,67	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	49	Thermal conductivity (W/(m*K))	
Connection	T/G	Weight per pallet (kg)	1102,5	Thermal resistance (m²*K)/W	
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	FSC™ Mix 70%	Antislip performance (DIN)	
Appearance	Golden floors	Biological durability	Class 1	Nobb.number	
Colour		Density	>= 500kg/m³	EAN Code	7035580211693



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.