



Beech Contract

Product details / Technical properties

Article number	10135569 (BD3L75TY)	Bevel	square edged	Moisture content	5-9%
Wood	Beech	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Contract	Surface structure	Unbrushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	1,89	PCP content	NPD
Format	Longstrip 21mm Longstrip Strongline	Boards per carton	4	Brinell Value (N/mm²)	37
Dimensions	13/16 x 8-15/32 x 86-5/8 inch	Weight per carton (kg)	21,5	Shrinking and swelling	
Top layer thickness	5,5 mm	m² per pallet	94,5	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K))	
Connection	T/G	Weight per pallet (kg)	1075	Thermal resistance (m²*K)/W	
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	FSC™ Mix 70%	Antislip performance (DIN)	R9
Appearance	Golden	Performance classification	Class 1	Nobb.number	
Colour		Density	>= 500kg/m³	EAN Code	7035580211549



www.blauer-engel.de/uz176

CE
06
Boen AS
Topstøttemoen 420-426, 4556 Trondheim, Norway
Parquet flooring according to EN 13489:2017-12 and EN 14342:2013 9,5-23 mm total thickness, parquet for indoor use.
DOP 4658, H6 0765
DL-16, EL density ~ 520kg/m³ thermal conductivity ~ 0,14 W/mK

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.