




Oak Contract

Product details / Technical properties

| | | | | | |
|----------------------------|--|-------------------------------------|--------------|---------------------------------------|---------------|
| Article number | 10135573 (EI3L75TY) | Bevel | square edged | Moisture content | 5-9% |
| Wood | Oak | Number of slotted top layers | 1 | Fire protection classification | Cfl-s1 |
| Grading | Contract | Surface structure | Unbrushed | Content of formaldehyde | E1 |
| Product type | 3-Layer | m² per carton | 1,89 | PCP content | NPD |
| Format | Longstrip 21mm Longstrip Strongline | Boards per carton | 4 | Brinell Value (N/mm²) | 38 |
| Dimensions | 13/16 x 8-15/32 x 86-5/8 inch | Weight per carton (kg) | 21,5 | Shrinking and swelling | |
| Top layer thickness | 0,217 mm | m² per pallet | 94,5 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | 50 | Thermal conductivity (W/(m*K)) | |
| Connection | T/G | Weight per pallet (kg) | 1075 | Thermal resistance (m²*K)/W | |
| Floor heating | conditionally suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 33 |
| Treatment | Live Matt lacquer | FSC claim | FSC™ Mix 70% | Antislip performance (DIN) | |
| Appearance | Golden | Performance classification | Class 1 | Nobb.number | 55774441 |
| Colour | | Density | >= 500kg/m³ | EAN Code | 7035580211723 |



www.blauer-engel.de/uz176



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.