

## Oak Authentic Vivo

10138098 (YEGVVKFD) Article number Oak Wood Grading Vivo Product type 3-layer parquet 14mm Plank Castle Format Dimensions 14 x 209 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Natural oil Appearance Golden floors Colour Authentic

Bevel
Number of slotted top laye
Surface structure
m <sup>2</sup> per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	beveled 2V
iyers	1
	deep brushed
	2,76
	6
	21,5
	138
	50
	1075
	EN 13489
	controlled sources
	Class 1
	>= 500kg/m³

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m <sup>2*</sup> K)/W	0,109
Antislip performance (CE)	USRV 45
Antislip performance (DIN)	R10
Nobb.number	56477714
EAN Code	7035580213147

REAL







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

