

Oak Transparent Adagio

Article number	10139205 (EB482KCD)	
Wood	Oak	
Grading	Adagio	
Product type	3-layer parquet	
Format	14mm Plank Chevron, A-Plank	
Dimensions	14 x 138 x 611 mm	
Top layer thickness	3,5 mm	
Core material	HDF / Spruce	
Connection	T/G	
Floor heating	suitable	
Treatment	Live Natural oil	
Appearance	Golden floors	
Colour	Transparent	

U
Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

beveled 4V
0
brushed
0,84
10
10
41,16
49
490
EN 13489
controlled sources
Class 1
>= 500kg/m ³

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,143
Thermal resistance (m ^{2*} K)/W	0,098
Antislip performance (CE)	USRV 45
Antislip performance (DIN)	R10
Nobb.number	56478686
EAN Code	7035580213772









	CE
	06
	Boen AS
To	pdalsveien 406-408, 4658 Tveit, Norway
8	Parquet flooring according to IN 13489: 2017-12 and EN 14342:2013 9.5-23 mm total thickness; parquet for indoor use
	DOP 4658; NB 0766
	Dfl-sl; EL density >= 500kg/m ^s thermal conductivity >= 0.14 W/mK

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

