

Article number	10139205 (EB482KCD)	Bevel	beveled 4V	Moisture content
Wood	Oak	Number of slotted top layers	0	Fire protection cla
Grading	Adagio	Surface structure	brushed	Content of formald
Product type	3-layer parquet	m² per carton	0,84	PCP content
Format	14mm Plank Chevron, A-Plank	Boards per carton	10	Brinell Value (N/m
Dimensions	14 x 138 x 611 mm	Weight per carton (kg)	10	Shrinking and swe
Top layer thickness	3,5 mm	m² per pallet	41,16	Breaking strength
Core material	HDF / Spruce	Boxes per pallet	49	Thermal conductiv


Connection T/G Floor heating suitable Treatment Live Natural oil

Appearance Golden floors Colour Transparent

Bevel				
Number of slotted top layers				
Surface structure				
m² per carton				
Boards per carton				
Weight per carton (kg)				
m² per pallet				
Boxes per pallet				
Weight per pallet (kg)				
EN Norm				
FSC claim				
Performance classification				

brushed 0,84
10
10
41,16
49
490
EN 13489
controlled sources
Class 1
>= 500kg/m³

Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,143
Thermal resistance (m²*K)/W	0,098
Antislip performance (CE)	USRV
Antislip performance (DIN)	R10
Nobb.number	56478



5-9%



Density











Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

