

Article number	10139210 / EB482KDD
Wood	Oak
Grading	Adagio
Product type	3-layer parquet
Format	14mm Plank Chevron, B-Plank
Dimensions	14 x 138 x 611 mm
Top layer thickness	3,5 mm

Core material

Connection

Floor heating

Appearance

Treatment

Colour

3,5 mm

HDF / Spruce

T/G

suitable

Live Natural oil

Golden floors

## Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim

Performance classification

brushed
0,84
10
10
41,16
49
490
EN 13489
controlled sources
Class 1
>= 500kg/m³

beveled 4V

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,143
Thermal resistance (m <sup>2*</sup> K)/W	0,098
Antislip performance (CE)	USRV 45
	Fire protection classification Content of formaldehyde PCP content Brinell Value Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W



Density









Antislip performance (DIN)

Nobb.number

EAN Code



R10

56478694

7035580213802

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

