

Article number	10139213 (EB482MDD)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Adagio	Surface structure	Brushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	0,84	PCP content	NPD
Format	14mm Plank Chevron, B-Plank	Boards per carton	10	Brinell Value (N/mm²)	38
Dimensions	9/16 x 5-7/16 x 24-1/16 inch	Weight per carton (kg)	10	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	41,16	Breaking strength	NPD
Core material	HDF / Spruce	Boxes per pallet	49	Thermal conductivity (W/(m*K)	0,143
Connection	T/G	Weight per pallet (kg)	490	Thermal resistance (m <sup>2</sup> *K)/W	0,098
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 45
Treatment	Live Natural oil White	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Light	Performance classification	Class 1	Nobb.number	56478713
Colour	White	Density	>= 500kg/m³	EAN Code	7035580213857















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

