



Oak Adagio

Product details / Technical properties

Article number	10142439 (EB482UCD)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	E 1
Grading	Adagio	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	0,84	PCP content	NPD
Format	14mm Plank Chevron, A-Plank	Boards per carton	10	Brinell Value (N/mm²)	38
Dimensions	14 x 138 x 611 mm	Weight per carton (kg)	10	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	41,16	Breaking strength	NPD
Core material	HDF / Spruce	Boxes per pallet	49	Thermal conductivity (W/(m*K))	0,143
Connection	T/G	Weight per pallet (kg)	490	Thermal resistance (m²*K)/W	0,098
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	
Treatment	unfinished	FSC claim	controlled sources	Antislip performance (DIN)	
Appearance		Biological durability	Class 1	Nobb.number	
Colour		Density	>= 500kg/m ³	EAN Code	7035580215233



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.