

## Oak Transparent Nature

Article number	10143424 (EIP2356D)	Bevel	square edged	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	2	Fire protection classification	Cfl-s1
Grading	Nature	Surface structure	Unbrushed	Content of formaldehyde	E1
Product type	2-Layer	m² per carton	2,63	PCP content	NPD
Format	Prestige	Boards per carton	80	Brinell Value (N/mm²)	38
Dimensions	3/8 x 2-3/4 x 18-1/2 inch	Weight per carton (kg)	15	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	94,68	Breaking strength	NPD
Core material	/ Spruce	Boxes per pallet	36	Thermal conductivity (W/(m*K)	0,13
Connection	T/G	Weight per pallet (kg)	540	Thermal resistance (m <sup>2*</sup> K)/W	0,08
Floor heating	very suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Golden	Performance classification	Class 1	Nobb.number	57724637
Colour	Transparent	Density	>= 500kg/m³	EAN Code	7035580216063

















Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

