

Oak Transparent Select

Article number	10143425 (EIP2256D)	
Wood	Oak	
Grading	Select	
Product type	2-layer parquet	
Format	10mm Strip Prestige	
Dimensions	10 x 70 x 470 mm	
Top layer thickness	3,5 mm	
Core material	/ Spruce	
Connection	T/G	
Floor heating	very suitable	
Treatment	Live Matt lacquer	
Appearance	Golden floors	
Colour	Transparent	

Bevel
Number of slotted top lay
Surface structure
m ² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

INSTITUT CERTIFIED PRODUCT ID 0218 - 33879 - 001

ers	2
	sanded
	2,63
	80
	15
	94,68
	36
	540
	EN 13489
	controlled sources

CO CERTIFIED BY SCS Global Services

Class 1 >= 500kg/m³

without bevel





	CE	
	06	
Boen AS		
To	pdalsveien 406-408, 4658 Tveit, Norway	
8	Parquet Rooring according to IN 13489: 2017-12 and EN 14342:2013 9.5-23 mm total thickness: parquet for indoor use	
	DOP 4658; NB 0766	
	Dfl-sl; El, density >= 500kg/m ³ thermal conductivity >= 0.14 W/mK	

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m ^{2*} K)/W	0,08
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	57724622
EAN Code	7035580216070