

15

36

540

EN 13489

Class 1

>= 500kg/m³

controlled sources

94,68

Oak Transparent Basic

Article number	10143428 (EIP2TK6D)
Wood	Oak
Grading	Basic
Product type	2-layer parquet
Format	10mm Strip Prestige
Dimensions	10 x 70 x 470 mm
Top layer thickness	3,5 mm
Core material	/ Spruce
Connection	T/G
Floor heating	very suitable
Treatment	Live Natural oil
Appearance	Golden floors
Colour	Transparent

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) **EN Norm** FSC claim **Biological durability** Density

Proc	duct defails / Technic
without bevel	Moisture content
2	Fire protection classification
sanded	Content of formaldehyde
2,63	PCP content
80	Brinell Value (N/mm²)

NPD 38 Shrinking and swelling NPD Breaking strength Thermal conductivity (W/(m*K) 0,13 Thermal resistance (m^{2*}K)/W 0,08 USRV 59 Antislip performance (CE) Antislip performance (DIN) R10 Nobb.number EAN Code 7035580216100

REAL INSTITUT CERTIFIED PRODUCT ID 0218 - 33879 - 001 CA CERTIFIED BY SCS Global Service



Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



chnical properties

5-9%

Cfl-s1

E 1