



Oak Transparent smoked Nature

Product details / Technical properties

Article number	10143435 (ELP23K6D)	Bevel	without bevel	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	2	Fire protection classification	Cfl-s1
Grading	Nature	Surface structure	sanded	Content of formaldehyde	E 1
Product type	2-layer parquet	m² per carton	2,63	PCP content	NPD
Format	10mm Strip Prestige	Boards per carton	80	Brinell Value (N/mm²)	38
Dimensions	10 x 70 x 470 mm	Weight per carton (kg)	15	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	94,68	Breaking strength	NPD
Core material	/ Spruce	Boxes per pallet	36	Thermal conductivity (W/(m*K))	0,133
Connection	T/G	Weight per pallet (kg)	540	Thermal resistance (m²*K)/W	0,075
Floor heating	very suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 59
Treatment	Live Natural oil	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Dark floors	Biological durability	Class 1	Nobb.number	
Colour	Transparent	Density	$\geq 500\text{kg/m}^3$	EAN Code	7035580216315



CERTIFIED BY
SCS Global Services



CE
06
Boen AS
Tordstovveien 406-408, 4458 Tvedt, Norway
Parquet flooring according to EN 13489:2017-12 and EN 14342:2015 5,5-23 mm total thickness parquet for indoor use
DOP 4658, NB 0766
Df: 41, E1 density $\approx 500\text{kg/m}^3$ thermal conductivity $\approx 0,13\text{ W/mK}$

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.