

WoodWalnut am.Number of slotted top layers2Fire protection classificationDfl-s1GradingNatureSurface structuresandedContent of formaldehydeE 1Product type2-layer parquetm² per carton2,63PCP contentNPDFormat10mm Strip PrestigeBoards per carton80Brinell Value (N/mm²)34Dimensions10 x 70 x 470 mmWeight per carton (kg)15Shrinking and swelling
Product type 2-layer parquet m² per carton 2,63 PCP content NPD Format 10mm Strip Prestige Boards per carton 80 Brinell Value (N/mm²) 34
Format 10mm Strip Prestige Boards per carton 80 Brinell Value (N/mm²) 34
,
Dimensions 10 x 70 x 470 mm Weight per carton (kg) 15 Shrinking and swelling
Top layer thickness3,5 mmm² per pallet94,68Breaking strengthNPD
Core material / Spruce Boxes per pallet 36 Thermal conductivity (W/(m*K) 0,14
Connection T/G Weight per pallet (kg) 540 Thermal resistance (m ^{2*} K)/W 0,07
Floor heating very suitable EN Norm EN 13489 Antislip performance (CE) USRV 33
Treatment Live Matt lacquer FSC claim controlled sources Antislip performance (DIN) R9
AppearanceBrown floorsBiological durabilityClass 1Nobb.number60760815
Colour Transparent Density >= 500kg/m³ EAN Code 7035580216209











Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

