Oak White Baltic

Product details / Technical properties

Article number	10143450 (EIP28M6D)
Wood	Oak
Grading	Baltic
Product type	2-layer parquet
Format	10mm Strip Prestige
Dimensions	10 x 70 x 470 mm
Top layer thickness	3,5 mm
Core material	/ Spruce
Connection	T/G
Floor heating	very suitable
Treatment	Live Natural oil white
Appearance	Light floors
Colour	White

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

without bevel	Moisture content	5-9%
2	Fire protection classification	Cfl-s1
unbrushed	Content of formaldehyde	E 1
2,63	PCP content	NPD
80	Brinell Value (N/mm²)	38
15	Shrinking and swelling	
94,68	Breaking strength	NPD
36	Thermal conductivity (W/(m*K)	0,13
540	Thermal resistance (m ^{2*} K)/W	0,08
EN 13489	Antislip performance (CE)	USRV
controlled sources	Antislip performance (DIN)	R10
Class 1	Nobb.number	
>= 500kg/m³	EAN Code	70355



USRV 59









Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

