

Article number	10145036 (EBG84MND)	Bevel	beveled 4V
Wood	Oak	Number of slotted top layers	0
Grading	Animoso	Surface structure	brushed
Product type	3-layer parquet	m² per carton	0.95
Format	14mm Plank Herringbone Click 138, B-Plank	Boards per carton	10

5G Click suitable Live Natural oil

Treatment Appearance Light floors Colour White

14 x 138 x 690 mm

HDF / Spruce

3.5 mm

Dimensions

Core material

Connection

Floor heating

Top layer thickness

Product details / Technical properties

Bevel	beveled 4V	Moisture content	5-9%
Number of slotted top layers	0	Fire protection classification	Dfl-s1
Surface structure	brushed	Content of formaldehyde	E 1
m² per carton	0.95	PCP content	NPD
Boards per carton	10	Brinell Value (N/mm²)	38
Weight per carton (kg)	11	Shrinking and swelling	
m² per pallet	46.55	Breaking strength	NPD
Boxes per pallet	49	Thermal conductivity (W/(m*K)	0.143
Weight per pallet (kg)	539	Thermal resistance (m ^{2*} K)/W	0.098
EN Norm	EN 13489	Antislip performance (CE)	USRV 45
FSC claim	controlled sources	Antislip performance (DIN)	R10
Performance classification	Class 1	Nobb.number	60093668
Density	>= 500kg/m³	EAN Code	7035580217602













Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

