

Article number	10146065 (YECXVKWD)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Canyon	Surface structure	Brushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton		PCP content	NPD
Format	Chalet	Boards per carton		Brinell Value (N/mm²)	38
Dimensions	3/4 x x inch	Weight per carton (kg)	11,152	Shrinking and swelling	
Top layer thickness	4,5 mm	m² per pallet	0	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet		Thermal conductivity (W/(m*K)	0,128
Connection	T/G	Weight per pallet (kg)	0	Thermal resistance (m ^{2*} K)/W	0,156
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 45
Treatment	Live Natural oil	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Golden	Performance classification	Class 1	Nobb.number	60093669
Colour	Authentic	Density	>= 500kg/m³	EAN Code	7035580218111















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

