Oak Animoso Product details / Technical properties Article number 10152329 (EIGV4KND) Bevel beveled 4V Moisture content 5-9% Number of slotted top layers Fire protection classification Dfl-s1 Grading Animoso Surface structure Unbrushed Content of formaldehyde E1 1,31 NPD Product type 3-Layer m² per carton **PCP** content 14mm Plank Herringbone Click Castle, B-Plank Brinell Value (N/mm²) 38 Format Boards per carton 9/16 x 8-1/4 x 41-1/8 Dimensions Weight per carton (kg) 15 Shrinking and swelling inch Top layer thickness m² per pallet 39,313 **Breaking strength** NPD Core material HDF / Spruce Boxes per pallet 30 Thermal conductivity (W/(m*K) 0,143 450 0,098 Connection 5G Click Weight per pallet (kg) Thermal resistance (m²*K)/W Floor heating suitable **EN Norm** EN 13489 Antislip performance (CE) USRV 59 Treatment Live Natural oil FSC claim controlled sources Antislip performance (DIN) R10

Class 1

>= 500kg/m³



Density

Performance classification







Nobb.number

EAN Code





7035580218869

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Appearance

Colour

Golden