



Oak Pale White Vivo

Product details / Technical properties

Article number	10152464 (PIG8V6ND)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Vivo	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	0,95	PCP content	NPD
Format	14mm Plank Herringbone Click 138, B-Plank	Boards per carton	10	Brinell Value (N/mm²)	38
Dimensions	14 x 138 x 690 mm	Weight per carton (kg)	11	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	46,55	Breaking strength	NPD
Core material	HDF / Spruce	Boxes per pallet	49	Thermal conductivity (W/(m*K))	0,143
Connection	5G Click	Weight per pallet (kg)	539	Thermal resistance (m²*K)/W	0,098
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 91
Treatment	Live Pure lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R11
Appearance	Light floors	Performance classification	Class 1	Nobb.number	60090270
Colour	Pale White	Density	>= 500kg/m³	EAN Code	7035580219354



www.blauer-engel.de/uz176

CE
06
Boen AS
Topdalsveien 426-428, 4556 Trondheim, Norway
Parquet flooring according to EN 13489:2013 and EN 14342:2013 9,5-23 mm total thickness, parquet for indoor use.
DOP 4658, H6 0765
Dk-h: EI, density ~ 520kg/m³ thermal conductivity ~ 0,14 W/mK

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.