



Oak Brazilian Brown Espresso

Product details / Technical properties

Article number	10155077 (PL4VZ3FE)	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Espressivo	Surface structure	Brushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	2,76	PCP content	NPD
Format	Castle plank	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions	9/16 x 8-1/4 x 86-5/8 inch	Weight per carton (kg)	21,8	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	138	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K))	0,129
Core material	Spruce / Spruce	Weight per pallet (kg)	1090	Thermal resistance (m²*K/W)	0,916
Condition	Product of nature – each tree is unique and individual colour combination will never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker.	EN Norm	EN 13489	Antislip performance (CE)	USR-V1
Floor heating	Suitable	ES Class	Class 1	Antislip performance (DIN)	R11
Treatment	UV-Burett, matt	Performance classification	Class 1	Nobb.number	
Appearance	Brown	Density	> 500kg/m ³	EAN Code	7035580221739



Generated 23.04.2026

boen.com



www.blauer-engel.de/uz176

