



Oak Transparent Espresso

Product details / Technical properties

Article number	10155081 (GG4VZ3FE)	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Espresso	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	2.76	PCP content	NPD
Format	14mm Plank Castle	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions	14 x 209 x 2200 mm	Weight per carton (kg)	21.8	Shrinking and swelling	
Top layer thickness	3.5 mm	m² per pallet	138	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K))	0.129
Connection	T/G	Weight per pallet (kg)	1090	Thermal resistance (m²*K)/W	0.109
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 91
Appearance	Golden floors	Performance classification	Class 1	Antislip performance (DIN)	1
Color	Translucent	Weight per pallet (kg)	1090	NOBB number	7035580221777
Color	Translucent	Weight per pallet (kg)	1090	EAN Code	7035580221777

We are a product of nature. Each tree has its own structure and individual colour combination. Antislip performance (DIN) will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Colored knots are filled with putty, so small gaps between the putty and wood may appear.



Generated 31.03.2026

www.blauer-engel.de/uz176