


Oak Authentic Vivo

| Article number | 10156623 |
|---------------------|----------------------|
| Wood | Oak |
| Grading | Vivo |
| Product type | 3-layer parquet |
| Format | 13.2mm Plank 181 |
| Dimensions | 13.2 x 181 x 2200 mm |
| Top layer thickness | 2,7 mm |
| Core material | Spruce / Spruce |
| Connection | 5G Click |
| Floor heating | suitable |
| Treatment | Live Natural oil |
| Appearance | Golden floors |
| Colour | Authentic |



>= 500kg/m³




| Moisture content | 5-9% |
|--|--|
| Fire protection classification | Dfl-s1 |
| Content of formaldehyde | E 1 |
| PCP content | NPD |
| Brinell Value (N/mm²) | 38 |
| Shrinking and swelling | |
| Breaking strength | NPD |
| Thermal conductivity (W/(m*K) | 0,127 |
| Thermal resistance (m ^{2*} K)/W | 0,104 |
| Antislip performance (CE) | USRV 45 |
| Antislip performance (DIN) | R10 |
| Nobb.number | 60090552 |
| EAN Code | 7035580224372 |
| | Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN) Nobb.number |

REAL







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

