

beveled 2V

brushed 3,19 8 23.5

127,6 40 940 EN 13489 controlled sources


Class 1 >= 500kg/m³

1

Oak Brown Jasper Vivo

Article number	10156624
Wood	Oak
Grading	Vivo
Product type	3-layer parquet
Format	13.2mm Plank 181
Dimensions	13.2 x 181 x 2200 mm
Top layer thickness	2,7 mm
Core material	Spruce / Spruce
Connection	5G Click
Floor heating	suitable
Treatment	Live Natural oil
Appearance	Dark floors
Colour	Brown Jasper

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density



Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,127
Thermal resistance (m²*K)/W	0,104
Antislip performance (CE)	USRV 45
Antislip performance (DIN)	R10
Nobb.number	60090670
EAN Code	7035580224389
	Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN) Nobb.number









Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

