



## Oak Honey Vivo

### Product details / Technical properties

|                            |                      |                                     |                    |                                       |               |
|----------------------------|----------------------|-------------------------------------|--------------------|---------------------------------------|---------------|
| <b>Article number</b>      | 10156625             | <b>Bevel</b>                        | beveled 2V         | <b>Moisture content</b>               | 5-9%          |
| <b>Wood</b>                | Oak                  | <b>Number of slotted top layers</b> | 1                  | <b>Fire protection classification</b> | Dfl-s1        |
| <b>Grading</b>             | Vivo                 | <b>Surface structure</b>            | brushed            | <b>Content of formaldehyde</b>        | E 1           |
| <b>Product type</b>        | 3-layer parquet      | <b>m² per carton</b>                | 3,19               | <b>PCP content</b>                    | NPD           |
| <b>Format</b>              | 13.2mm Plank 181     | <b>Boards per carton</b>            | 8                  | <b>Brinell Value (N/mm²)</b>          | 38            |
| <b>Dimensions</b>          | 13.2 x 181 x 2200 mm | <b>Weight per carton (kg)</b>       | 23,5               | <b>Shrinking and swelling</b>         |               |
| <b>Top layer thickness</b> | 2,7 mm               | <b>m² per pallet</b>                | 127,6              | <b>Breaking strength</b>              | NPD           |
| <b>Core material</b>       | Spruce / Spruce      | <b>Boxes per pallet</b>             | 40                 | <b>Thermal conductivity (W/(m*K))</b> | 0,127         |
| <b>Connection</b>          | 5G Click             | <b>Weight per pallet (kg)</b>       | 940                | <b>Thermal resistance (m²*K)/W</b>    | 0,104         |
| <b>Floor heating</b>       | suitable             | <b>EN Norm</b>                      | EN 13489           | <b>Antislip performance (CE)</b>      | USRV 45       |
| <b>Treatment</b>           | Live Natural oil     | <b>FSC claim</b>                    | controlled sources | <b>Antislip performance (DIN)</b>     | R10           |
| <b>Appearance</b>          | Golden floors        | <b>Performance classification</b>   | Class 1            | <b>Nobb.number</b>                    | 60090667      |
| <b>Colour</b>              | Honey                | <b>Density</b>                      | >= 500kg/m³        | <b>EAN Code</b>                       | 7035580224396 |



[www.blauer-engel.de/uz176](http://www.blauer-engel.de/uz176)



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.