

Oak Pearl Animoso

Product details / Technical properties

Article number	10156777	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Animoso	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	3,19	PCP content	NPD
Format	13.2mm Plank 181	Boards per carton	8	Brinell Value (N/mm²)	38
Dimensions	13.2 x 181 x 2200 mm	Weight per carton (kg)	23,5	Shrinking and swelling	
Top layer thickness	2,7 mm	m² per pallet	127,6	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	40	Thermal conductivity (W/(m*K))	0,127
Connection	5G Click	Weight per pallet (kg)	940	Thermal resistance (m²*K)/W	0,104
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 59
Treatment	Live Natural oil	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Light floors	Performance classification	Class 1	Nobb.number	60090550
Colour	Pearl	Density	>= 500kg/m ³	EAN Code	7035580224969



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.