

Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Animoso	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	1,31	PCP content	NPD
Format	14mm Plank Herringbone Click Castle, A-Plank	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions	14 x 209 x 1045 mm	Weight per carton (kg)	15,5	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	39,3	Breaking strength	NPD
Core material	HDF / Spruce	Boxes per pallet	30	Thermal conductivity (W/(m*K)	0,143
Connection	5G Click	Weight per pallet (kg)	465	Thermal resistance (m ^{2*} K)/W	0,098

EN 13489

Class 1

>= 500kg/m³

controlled sources



suitable

Live Pure lacquer

Golden floors

Transparent



EN Norm

FSC claim

Density

Performance classification









Antislip performance (CE)

Antislip performance (DIN)

Nobb.number

EAN Code



USRV 91 R11

53111058

7035580225386

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Floor heating

Appearance

Treatment

Colour