

Article number	10159955	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Boulevard	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	2,84	PCP content	NPD
Format	13.2mm 3-Strip	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions	13.2 x 215 x 2200 mm	Weight per carton (kg)	21,5	Shrinking and swelling	
Top layer thickness	2,7 mm	m² per pallet	142	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K)	0,127
Connection	5G Click	Weight per pallet (kg)	1075	Thermal resistance (m <sup>2*</sup> K)/W	0,104
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 94
Treatment	ultra-matt lacquered	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Grey floors	Biological durability	Class 1	Nobb.number	
Colour	Rustic Basalt	Density	>= 500kg/m <sup>3</sup>	EAN Code	7035580228066













Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

