

## Oak Raw Look Town

Article number	10159961	
Wood	Oak	
Grading	Town	
Product type	3-layer parquet	
Format	13.2mm Plank 181	
Dimensions	13.2 x 181 x 2200 mm	
Top layer thickness	2,7 mm	
Core material	Spruce / Spruce	
Connection	5G Click	
Floor heating	suitable	
Treatment	ultra-matt lacquered	
Appearance	Golden floors	
Colour	Raw Look	

## Bevel Number of slotted top lay Surface structure m<sup>2</sup> per carton Boards per carton (kg) m<sup>2</sup> per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim Biological durability Density

	beveled 2V
top layers	1
	brushed
	3,19
n	8
n (kg)	23,5
	127,6
	40
(kg)	940
	EN 13489
	controlled sources
ility	Class 1

>= 500kg/m<sup>3</sup>



Moisture co	ontent	5-9%
Fire protect	tion classification	Dfl-s1
Content of	formaldehyde	E 1
PCP conter	nt	NPD
Brinell Valu	e (N/mm²)	38
Shrinking a	ind swelling	
Breaking st	rength	NPD
Thermal co	nductivity (W/(m*K)	0,127
Thermal res	sistance (m²*K)/W	0,104
Antislip per	formance (CE)	USRV 94
Antislip per	formance (DIN)	R10
Nobb.num	ber	
EAN Code		7035580228127

REAL

 TESTED PRODUCT

 10 0921 - 33879 - 003





Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

