

Oak Lime Stone Town

| Article number | 10159962 |
|---------------------|----------------------|
| Wood | Oak |
| Grading | Town |
| Product type | 3-layer parquet |
| Format | 13.2mm Plank 181 |
| Dimensions | 13.2 x 181 x 2200 mm |
| Top layer thickness | 2,7 mm |
| Core material | Spruce / Spruce |
| Connection | 5G Click |
| Floor heating | suitable |
| Treatment | ultra-matt lacquered |
| Appearance | Grey floors |
| Colour | Lime Stone |

| Bevel |
|------------------------------|
| Number of slotted top layers |
| Surface structure |
| m² per carton |
| Boards per carton |
| Weight per carton (kg) |
| m² per pallet |
| Boxes per pallet |
| Weight per pallet (kg) |
| EN Norm |
| FSC claim |
| Biological durability |
| Density |

| beveled 2V | Мо |
|------------|------|
| 1 | Fire |
| brushed | Co |
| 3,19 | PC |
| 8 | Brir |
| 23,5 | Shr |
| 127,6 | Bre |
| 40 | The |
| 940 | The |
| EN 13489 | Ant |

controlled sources

Class 1 >= 500kg/m³ Product details / Technical properties

| Moisture content | 5-9% |
|--|---------------|
| Fire protection classification | Dfl-s1 |
| Content of formaldehyde | E 1 |
| PCP content | NPD |
| Brinell Value (N/mm²) | 38 |
| Shrinking and swelling | |
| Breaking strength | NPD |
| Thermal conductivity (W/(m*K) | 0,127 |
| Thermal resistance (m ^{2*} K)/W | 0,104 |
| Antislip performance (CE) | USRV 94 |
| Antislip performance (DIN) | R10 |
| Nobb.number | |
| EAN Code | 7035580228134 |

REAL







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

