

beveled 2V Article number 10159964 Bevel Moisture content 5-9% Dfl-s1 Wood Oak Number of slotted top layers Fire protection classification Grading Character Surface structure brushed Content of formaldehyde E 1 Product type 3-layer parquet m² per carton 3,19 **PCP** content NPD 13.2mm Plank 181 8 Brinell Value (N/mm²) Format Boards per carton 38 23.5 Shrinking and swelling Dimensions 13.2 x 181 x 2200 mm Weight per carton (kg) 127,6 **Top layer thickness** 2,7 mm m² per pallet **Breaking strength** Core material Spruce / Spruce Boxes per pallet 40 Thermal conductivity (W/(m*K) Connection 5G Click Weight per pallet (kg) 940 Thermal resistance (m^{2*}K)/W 0,104 EN 13489 USRV 33 Floor heating suitable EN Norm Antislip performance (CE) Antislip performance (DIN) Treatment natural oiled FSC claim controlled sources R9 Appearance Golden floors Performance classification Class 1 Nobb.number Colour Transparent Density >= 500kg/m³ **EAN Code** 7035580228158














Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

