

Oak White Village

Product details / Technical properties

Article number	10159968	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	3	Fire protection classification	Dfl-s1
Grading	Village	Surface structure	brushed	Content of formaldehyde	El
Product type	3-layer parquet	m² per carton	3,04	PCP content	NPD
Format	13.2mm Plank 138	Boards per carton	10	Brinell Value (N/mm²)	38
Dimensions	13.2 x 138 x 2200 mm	Weight per carton (kg)	23	Shrinking and swelling	
Top layer thickness	2,7 mm	m² per pallet	127,68	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	42	Thermal conductivity (W/(m*K)	0,127
Connection	5G Click	Weight per pallet (kg)	966	Thermal resistance (m ² *K)/W	0,104
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	natural oiled	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Light floors	Biological durability	Class 1	Nobb.number	
Colour	White	Density	>= 500kg/m³	EAN Code	7035580228196







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

