



Oak Transparent Basic

Product details / Technical properties

| | | | | | |
|----------------------------|---------------------|-------------------------------------|-------------------------|-----------------------------------------------|---------------|
| Article number | 10161944 | Bevel | without bevel | Moisture content | 5-9% |
| Wood | Oak | Number of slotted top layers | 2 | Fire protection classification | Cfl-s1 |
| Grading | Basic | Surface structure | sanded | Content of formaldehyde | E 1 |
| Product type | 2-layer parquet | m² per carton | 2.63 | PCP content | NPD |
| Format | 10mm Strip Prestige | Boards per carton | 80 | Brinell Value (N/mm²) | 38 |
| Dimensions | 10 x 70 x 470 mm | Weight per carton (kg) | 14.5 | Shrinking and swelling | |
| Top layer thickness | 3.5 mm | m² per pallet | 94.68 | Breaking strength | NPD |
| Core material | / Spruce | Boxes per pallet | 36 | Thermal conductivity (W/(m*K)) | 0.13 |
| Connection | T/G | Weight per pallet (kg) | 522 | Thermal resistance (m²*K)/W | 0.08 |
| Floor heating | very suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 33 |
| Treatment | Live Matt lacquer | FSC claim | FSC@ 100% | Antislip performance (DIN) | R9 |
| Appearance | Golden floors | Performance classification | Class 1 | Nobb.number | 60760809 |
| Colour | Transparent | Density | >= 500kg/m ³ | EAN Code | 7035580228851 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.