



Oak Soft Brown Andante

Product details / Technical properties

Article number	10163212	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Andante	Surface structure	brushed	Content of formaldehyde	E 1
Product type	2-layer parquet	m² per carton	3,25	PCP content	<=5 ppm
Format	Herringbone T/G	Boards per carton	30	Brinell Value (N/mm²)	38
Dimensions	10,5 x 137 x 790 mm	Weight per carton (kg)	19	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	104	Breaking strength	NPD
Core material	/ Spruce	Boxes per pallet	32	Thermal conductivity (W/(m*K))	0,132
Connection	T/G	Weight per pallet (kg)	608	Thermal resistance (m²*K)/W	0,079
Floor heating	very suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 57
Treatment	Live Matt Plus lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Brown floors	Biological durability	Class 1	Nobb.number	
Colour	Soft Brown	Density	>= 500kg/m³	EAN Code	7611661203254



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.