



Oak White Structure

Product details / Technical properties

Article number	10163865	Bevel	square edged	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	2	Fire protection classification	Cfl-s1
Grading	Structure	Surface structure	sanded	Content of formaldehyde	E1
Product type	2-Layer	m² per carton	2,63	PCP content	NPD
Format	Prestige	Boards per carton	80	Brinell Value (N/mm²)	38
Dimensions	3/8 x 2-3/4 x 18-1/2 inch	Weight per carton (kg)	14,5	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	94,68	Breaking strength	NPD
Core material	/ Spruce	Boxes per pallet	36	Thermal conductivity (W/(m*K))	0,133
Connection	T/G	Weight per pallet (kg)	522	Thermal resistance (m²*K)/W	0,075
Floor heating	very suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Light	Performance classification	Class 1	Nobb.number	60760817
Colour	White	Density	>= 500kg/m ³	EAN Code	7035580230809



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.