

Oak Transparent Andante

Article number 10036247 (EBGV33FD) Wood Oak Grading Andante Product type 3-layer parquet 14mm Plank Castle Format 14 x 209 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Pure lacquer Appearance Golden floors Colour Transparent

Bevel Number of slotted top lay Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim Biological durability Density

	beveled 2V
layers	1
	brushed
	2,76
	6
g)	21,5
	138
	50
)	1075
	EN 13489
	controlled sources
	Class 1

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m ^{2*} K)/W	0,109
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	49254126
EAN Code	7035580173977



>= 500kg/m³

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

