

Wood   Oak   Number of slotted top layers   1   Fire protection classification     Grading   Animoso   Surface structure   brushed   Content of formaldehyde     Product type   3-layer parquet   m² per carton   2,76   PCP content	Dfl-s1 E 1 NPD 38
·	NPD
Product type3-layer parquetm² per carton2,76PCP content	
	38
Format 14mm Plank Castle Boards per carton 6 Brinell Value (N/mm²)	
Dimensions 14 x 209 x 2200 mm Weight per carton (kg) 21,5 Shrinking and swelling	
Top layer thickness 3,5 mm m² per pallet 138 Breaking strength	NPD
Core material Spruce / Spruce Boxes per pallet 50 Thermal conductivity (W/(m*K)	0,129
Connection 5G Click Weight per pallet (kg) 1075 Thermal resistance (m <sup>2*</sup> K)/W	0,109
Floor heating suitable EN Norm EN 13489 Antislip performance (CE)	USRV 45
Treatment Live Natural oil white FSC claim controlled sources Antislip performance (DIN)	R10
Appearance       Light floors       Biological durability       Class 1       Nobb.number	49254115
Colour White Density >= 500kg/m³ EAN Code	7035580085690














Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

