



Oak White Animoso

Product details / Technical properties

| | | | | | |
|----------------------------|-----------------------------|-------------------------------------|-------------------------|-----------------------------------------------|---------------|
| Article number | 10036867 (EIG842PD) | Bevel | square edged | Moisture content | 5-9% |
| Wood | Oak | Number of slotted top layers | 2 | Fire protection classification | Cfl-s1 |
| Grading | Animoso | Surface structure | sanded | Content of formaldehyde | E1 |
| Product type | 3-Layer | m² per carton | 3,04 | PCP content | NPD |
| Format | 5-1/2" plank | Boards per carton | 10 | Brinell Value (N/mm²) | 38 |
| Dimensions | 9/16 x 5-7/16 x 86-5/8 inch | Weight per carton (kg) | 25,5 | Shrinking and swelling | |
| Top layer thickness | 3,5 mm | m² per pallet | 127,68 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | 42 | Thermal conductivity (W/(m*K)) | 0,129 |
| Connection | 5G@ Click | Weight per pallet (kg) | 1071 | Thermal resistance (m²*K)/W | 0,109 |
| Floor heating | suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 33 |
| Treatment | Live Matt lacquer | FSC claim | controlled sources | Antislip performance (DIN) | R9 |
| Appearance | Light | Performance classification | Class 1 | Nobb.number | 53111058 |
| Colour | White | Density | >= 500kg/m ³ | EAN Code | 7035580070887 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.