

## Oak Pearl Animoso


Article number 10037193 (ORG84MFD) Wood Oak Grading Animoso Product type 3-layer parquet 14mm Plank 138 Format 14 x 138 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Live Natural oil Treatment Appearance Light floors Colour Pearl

Bevel
Number of slotted top lay
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

INSTITUT

TESTED PRODUCT

ID 0921 - 33879 - 003



beveled 2V	Moisture conte
2	Fire protection
unbrushed	Content of form
3,04	PCP content
10	Brinell Value (I
22,7	Shrinking and
127,68	Breaking stren
42	Thermal condu
953,4	Thermal resista
EN 13489	Antislip perform
controlled sources	Antislip perform
Class 1	Nobb.number
>= 500kg/m³	EAN Code

ore

C CERTIFIED BY SCS Global Service





Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

de/uz176



## Product details / Technical properties

sture content	5-9%
protection classification	Dfl-s1
tent of formaldehyde	E 1
content	NPD
ell Value (N/mm²)	38
nking and swelling	
iking strength	NPD
mal conductivity (W/(m*K)	0,129
mal resistance (m²*K)/W	0,109
slip performance (CE)	USRV 59
slip performance (DIN)	R10
b.number	45965114
Code	703558008073