

Oak Oregon Andante

Article number 10041716 (EYGL35TD) Oak Wood Grading Andante Product type 3-layer parquet 14mm Longstrip 3-Strip Format 14 x 215 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Dark floors Colour Oregon

Bevel
Number of slotted top lay
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	square edged
ayers	0
	unbrushed
	2,84
	6
	21
	142
	50
	1050
	EN 13489
	controlled sources
	Class 1
	>= 500kg/m³

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m ^{2*} K)/W	0,11
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	53111058
EAN Code	7035580185178











Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

