

Article number	10041721 (ETGL35TD)	
Wood	Oak	
Grading	Andante	
Product type	3-layer parquet	
Format	14mm Longstrip 3-Strip	
Dimensions	14 x 215 x 2200 mm	
Top layer thickness	3,5 mm	
Core material	Spruce / Spruce	
Connection	5G Click	
Floor heating	suitable	
Treatment	Live Matt lacquer	
Appearance	Golden floors	
Colour	Toscana	

raarrio
Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability

square edged
0
unbrushed
2,84
6
21
142
50
1050
EN 13489
controlled sources
Class 1
>= 500kg/m³

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m ^{2*} K)/W	0,11
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	53111058



Density







EAN Code





7035580186304

Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

