

## Oak Transparent Finale

10041808 (EIGLTKTD) Article number Oak Wood Grading Finale Product type 3-layer parquet 14mm Longstrip 3-Strip Format Dimensions 14 x 215 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Natural oil Appearance Golden floors Colour Transparent

Bevel
Number of slotted top laye
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
<b>Biological durability</b>
Density

	without bevel
ayers	0
	unbrushed
	2,84
	6
	21
	142
	50
	1050
	EN 13489
	controlled source
	Class 1

>= 500kg/m<sup>3</sup>



Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m <sup>2*</sup> K)/W	0,109
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	50693697
EAN Code	7035580186465







	CE
	06
	Boen AS
To	pdalsvelen 406-408, 4658 Tveit, Norway
E	Parquet Rooring according to N 13489: 2017-12 and EN 14342:2013 9.5-23 mm total thickness: parquet for indoor use
	DOP 4658; NB 0766
	Dfl-sl; El, density >= 500kg/m <sup>s</sup> thermal conductivity >= 0.14 W/mK

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

