

Oak Arizona Concerto

10041988 (EQG875PD) Article number Oak Wood Grading Concerto Product type 3-layer parquet 14mm Plank 138 Format Dimensions 14 x 138 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Grey floors Colour Arizona

Bevel
Number of slotted top lo
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	without bevel	
otted top layers	2	
cture	unbrushed	
n	3,04	
arton	10	
arton (kg)	23,3	
ł	127,68	
allet	42	
allet (kg)	978,6	
	EN 13489	
	controlled sources	
urability	Class 1	

Product	details /	Technical	properties
---------	-----------	-----------	------------

Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m ² *K)/W	0,109
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	53089555
EAN Code	7035580187578
	Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN) Nobb.number



>= 500kg/m³

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

