

Article number 10114	4702 (EBGLT3TD)	Bevel	without bevel	Moisture content	5-9%
Wood Oak	:	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading Finale	le	Surface structure	brushed	Content of formaldehyde	E 1
Product type 3-lay	yer parquet	m² per carton	2,84	PCP content	NPD
Format 14mm	m Longstrip 3-Strip	Boards per carton	6	Brinell Value (N/mm²)	38
Dimensions 14 x 2	215 x 2200 mm	Weight per carton (kg)	21	Shrinking and swelling	
Top layer thickness 3,5 m	nm	m² per pallet	142	Breaking strength	NPD
Core material Sprud	ice / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K)	0,13
Connection 5G C	Click	Weight per pallet (kg)	1050	Thermal resistance (m ^{2*} K)/W	0,11
Floor heating suital	able	EN Norm	EN 13489	Antislip performance (CE)	USRV 91
Treatment Live F	Pure lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R11
Appearance Gold	den floors	Biological durability	Class 1	Nobb.number	52000264
Colour Trans	sparent	Density	>= 500kg/m³	EAN Code	7035580199939
















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

