

Article number	10125683 (EIO23K6D)	Bevel	without bevel	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	2	Fire protection classification	Cfl-s1
Grading	Nature	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	2-layer parquet	m² per carton	2,24	PCP content	NPD
Format	12.5mm Strip Traffic	Boards per carton	68	Brinell Value (N/mm²)	38
Dimensions	12.5 x 70 x 470 mm	Weight per carton (kg)	16,5	Shrinking and swelling	
Top layer thickness	5,5 mm	m² per pallet	80,64	Breaking strength	NPD
Core material	/ Spruce	Boxes per pallet	36	Thermal conductivity (W/(m*K)	0,14
Connection	T/G	Weight per pallet (kg)	594	Thermal resistance (m <sup>2*</sup> K)/W	0,09
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 59
Treatment	Live Natural oil	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Golden floors	Biological durability	Class 1	Nobb.number	
Colour	Transparent	Density	>= 500kg/m³	EAN Code	7035580211389













Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

