

## Oak Transparent Basic

Article number	10125684 (EIO2TK6D)
Wood	Oak
Grading	Basic
Product type	2-layer parquet
Format	12.5mm Strip Traffic
Dimensions	12.5 x 70 x 470 mm
Top layer thickness	5,5 mm
Core material	/ Spruce
Connection	T/G
Floor heating	suitable
Treatment	Live Natural oil
Appearance	Golden floors
Colour	Transparent

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

square edged
2
unbrushed
2,24
68
16,5
80,64
36
594
EN 13489
controlled sources
Class 1

>= 500kg/m<sup>3</sup>



Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,14
Thermal resistance (m <sup>2*</sup> K)/W	0,09
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	
EAN Code	7035580211396

REAL







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

