

Oak White Traditional

10126733 (EI1Y4MWD) Article number Oak Wood Grading Traditional Product type 3-layer parquet Format 15mm Plank Chaletino Dimensions 15 x 300 x 2750 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection T/G Floor heating suitable Treatment Live Natural oil white Appearance Light floors Colour White

Bevel
Number of slotted top lay
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	beveled 4V
op layers	0
	unbrushed
	1,65
	2
(kg)	14
	64,35
	39
(g)	546
	EN 13489
	controlled sources
у	Class 1
	>= 500kg/m³

Product details /	Technical	properties
-------------------	-----------	------------

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,128
Thermal resistance (m ^{2*} K)/W	0,117
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	55472824
EAN Code	7035580210368





Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

