

beveled 4V

unbrushed 0,95

0

10

11 46,55 49 539 EN 13489 controlled sources

Class 1

>= 500kg/m<sup>3</sup>

## Oak Transparent Adagio

Article number	10126790 (EIG82KND)	
Wood	Oak	
Grading	Adagio	
Product type	3-layer parquet	
Format	14mm Plank Herringbone Click 138, B-Plank	
Dimensions	14 x 138 x 690 mm	
Top layer thickness	3,5 mm	
Core material	HDF / Spruce	
Connection	5G Click	
Floor heating	suitable	
Treatment	Live Natural oil	
Appearance	Golden floors	
Colour	Transparent	

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

## Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,143
Thermal resistance (m <sup>2*</sup> K)/W	0,098
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	55493964
EAN Code	7035580210597







CE	
06	
Boen AS	
Topdalsveien 406-408, 4658 Tveit, Norway	
Parquet flooring according to EN 13489: 2017-12 and EN 14342-2013 9.5-23 mm total thickness parquet for indoor use	
DOP 4658; NB 0766	
Dfl-sl; El, density >= 500kg/m <sup>4</sup> thermal conductivity >= 0.14 W/mK	

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

