

## Oak Adagio

## Product details / Technical properties

Article number	10141606 (EBG82UND)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	
Grading	Adagio	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	0,95	PCP content	NPD
Format	14mm Plank Herringbone Click 138, B-Plank	Boards per carton	10	Brinell Value (N/mm²)	38
Dimensions	14 x 138 x 690 mm	Weight per carton (kg)	11	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	46,55	Breaking strength	NPD
Core material	HDF / Spruce	Boxes per pallet	49	Thermal conductivity (W/(m*K)	0,143
Connection	5G Click	Weight per pallet (kg)	539	Thermal resistance (m <sup>2</sup> *K)/W	0,098
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	
Treatment	unfinished	FSC claim	controlled sources	Antislip performance (DIN)	
Appearance		Biological durability	Class 1	Nobb.number	
Colour		Density	>= 500kg/m³	EAN Code	7035580214786



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

