

Oak Transparent Basic

Article number 10143418 (EIP2T56D) Oak Wood Grading Basic Product type 2-layer parquet Format 10mm Strip Prestige 10 x 70 x 470 mm Dimensions Top layer thickness 3,5 mm Core material / Spruce Connection T/G Floor heating very suitable Treatment Live Matt lacquer Appearance Golden floors Colour Transparent

Bevel
Number of slotted top lay
Surface structure
m ² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

INSTITUT CERTIFIED PRODUCT ID 0218 - 33879 - 001

er of slotted top layers				
e structure				
r carton				
s per carton				
it per carton (kg)				
r pallet				
per pallet				
t per pallet (kg)				
rm				
aim				
jical durability				
hz				



C CERTIFIED BY SCS Global Service





CE			
	06		
	Boen AS		
To	pdalsveien 406-408, 4658 Tveit, Norway		
1	Parquet flooring according to EN 13489: 2017-12 and EN 14342 2013 9.5-23 mm total thickness: parquet for indoor use		
	DOP 4658; NB 0766		
	Dfl-sl; EL density >= 500kg/m ^s thermal conductivity >= 0.14 W/mK		

Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m ^{2*} K)/W	0,08
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	57724641
EAN Code	703558021604